

10-A198 365


TUTORIAL TRACK I INTRODUCTION TO ADA(U) INFORMATION  
SYSTEMS AND TECHNOLOGY CENTER W-P AFB OH ADA VALIDATION  
FACILITY C ENGLE ET AL 89 JUN 87


1/2

UNCLASSIFIED

F/G 12/5

NL





MICROCOPY RESOLUTION TEST CHART  
NATIONAL BUREAU OF STANDARDS-1963-A

AD-A-190 365

TUTORIAL

TRACK I

INTRODUCTION TO ADA

By

Major Charles Engle, U.S. Military Academy

and

Lieutenant Tony Dominice, Keesler Air Force Base

12 22 34 2

UNCLASSIFIED

DTIC FILE COPY

(When Data Entered)

AD-A190 365

## ACTION PAGE

READ INSTRUCTIONS  
BEFORE COMPLETING FORM

12. GOVT ACCESSION NO.

3. RECIPIENT'S CATALOG NUMBER

2

Tutorial Track I. Introduction to Ada

5. TYPE OF REPORT & PERIOD COVERED  
Tutorial, 9 June, 1987

6. PERFORMING ORG. REPORT NUMBER

7. AUTHOR(s)

MAJ Charles Engle, and LT Tony Dominice

8. CONTRACT OR GRANT NUMBER(s)

9. PERFORMING ORGANIZATION AND ADDRESS

Ada Software Education and Training Team  
Ada Joint Program Office, 3E114, The  
Pentagon, Washington, D.C. 20301-308110. PROGRAM ELEMENT, PROJECT, TASK  
AREA & WORK UNIT NUMBERS

11. CONTROLLING OFFICE NAME AND ADDRESS

Ada Joint Program Office  
3E 114, The Pentagon  
Washington, DC 20301-3081

12. REPORT DATE

June 9, 1987

13. NUMBER OF PAGES

124

14. MONITORING AGENCY NAME &amp; ADDRESS (If different from Controlling Office)

Ada Joint Program Office

15. SECURITY CLASS (of this report)  
UNCLASSIFIED15a. SECURITY CLASSIFICATION DOWNGRADING  
N/A

16. DISTRIBUTION STATEMENT (of this Report)

Approved for public release; distribution unlimited.

17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20. If different from Report)

UNCLASSIFIED

DTIC

ELECTE

JAN 06 1988

18. SUPPLEMENTARY NOTES

19. KEYWORDS (Continue on reverse side if necessary and identify by block number)

Ada Programming language, Ada Training, Education, Training, Computer  
Programs, Ada Joint Program Office, AJPO

20. ABSTRACT (Continue on reverse side if necessary and identify by block number)

This document contains prints of viewgraphs presented at the  
Introduction to Ada Tutorial, Track I June 9, 1987. Topics covered  
were The Software Crisis, Technical Background, Basic Constructs,  
Subprograms, Generics and Tasks.

DD FORM 1473

1 JAN 73

EDITION OF 1 NOV 65 IS OBSOLETE

S/N 0102-LF-014-6601

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

# Introduction to Ada<sup>®</sup>

MAJOR CHUCK ENGLE

LT TONY DOMINICE

UNITED STATES MILITARY ACADEMY

3390 TECH TRAINING GROUP

DEPARTMENT OF GEOGRAPHY AND

STARS TRAINING SECTION

COMPUTER SCIENCE

KEESLER AFB, MS. 39534

WEST POINT, N.Y. 10996



®

Ada is a registered Trademark of the U.S. Government (AJPO)

A-1

# OVERVIEW

- I. The Software Crisis
- II. Program Units
- III. Types
- IV. Control Statements
- V. Exceptions
- VI. Generics
- VII. Tasks
- VIII. Application Example

# Types

## Records

```
A_DRIVER : INSURANCE (GOOD);  
ANOTHER : INSURANCE (BAD);
```

```
begin
```

```
  A_DRIVER.NORMAL_RATE := 25;  
  A_DRIVER.DISCOUNT_RATE := 0.15;
```

```
  ANOTHER.NORMAL_RATE := 25;  
  ANOTHER.ADDITIONAL := 10;
```

# Types


## Access

- Pointer variables
- Allow for dynamic allocation of memory
- Objects created via an allocator

type POINTER is access INTEGER;

X, Y : POINTER;    -- initialized to  
                    -- null

begin




X := new INTEGER;    -- allocate  
                    -- memory to X



X.all := 32;    -- place 32 in the  
                    -- location pointed to  
                    -- by X



Y := X;    -- X and Y point to the same  
            -- location





# Software Crisis


- Rising costs of software
- Unreliable
- Late
- Not maintainable
- Inefficient
- Not transportable

WHY??

- Too many languages
- Poor tools
- Changing technology
- Not enough trained people


INABILITY TO MANAGE COMPLEX PROBLEMS

# Software Crisis



# Software Crisis


DoD Embedded Hardware/Software Costs




DEMAND FOR NEW SOFTWARE

50  
40  
30  
20  
10

ANNUAL PERCENTAGE INCREASES  
(USING 1980 AS A BASELINE)



# Software Crisis



# Software Crisis

## EMBEDDED SYSTEMS

- Large
- Long lived
- Continous change
- Physical constraints
- High reliability

## EMBEDDED SYSTEMS SOFTWARE

- Severe reliability requirements
- Time and size constraints
- Parallel processing
- Real time control
- Exception handling
- Unique I/O

# Software Crisis

## SOLUTIONS

<u>Single Language</u>	<u>Improved Tools</u>	<u>Improved Methodologies</u>
------------------------	-----------------------	-------------------------------

Ada	Ada	Methodman
-----	-----	-----------

	APSE	??
--	------	----

(Ada		
------	--	--


Program ming		
--------------	--	--

Support		
---------	--	--

Environment )		
---------------	--	--

SOFTWARE ENGINEERING
----------------------

# Software Crisis



Ada Joint Program Office

ANSI/MIL STD 1815A FEB 83

First Translator APR 83



# Software Crisis


Ada Programming Support Environment

1978 SANDMAN

PEBBLEMAN

1980 STONEMAN

- Software developer productivity
- Retraining costs
- Lack of tools
- Lack of standardization



# Software Crisis

"The basic problem is not our mismanagement of technology, but rather our inability to manage the complexity of our systems."

--- E.G. Booch

## SOFTWARE ENGINEERING

### GOALS


- Understandability
- Modifiability
- Reliability
- Efficiency

### PRINCIPLES


- Abstraction
- Information Hiding
- Modularity
- Localization
- Completeness
- Confirmability
- Consistency

# Program Units

-- Ada software systems consist of one or more program units




# Program Units




Structuring tool

task



Parallel processing

# Program Units



"what" the program unit does  $\longleftrightarrow$  ABSTRACTION  $\Longrightarrow$  "how" the program unit does what it does


all the user of the program unit needs to know  $\longleftrightarrow$  INFORMATION HIDING  $\Longrightarrow$  the details of implementation are inaccessible to the user

# Program Units

By separating the "what" from the "how"...



we decrease the complexity of the system...




and increase: UNDERSTANDABILITY  
MODIFIABILITY

# Program Units

## Subprograms

- Executable routines
- Main program
- Recursive



### PROCEDURE

-- Defines an action to be performed

```
procedure GET_NAME ( NAME : out STRING );
```

```
    GET_NAME ( PERSONS_NAME );
```

### FUNCTION

-- Returns a value

```
function SIN ( ANGLE : in RADIANS ) return FLOAT;
```

```
    ANGLE_SIN := SIN ( 2 );
```



# Program Units

## Procedures

### SPECIFICATION

- Defines name
- Defines parameters to be passed

```
procedure ADD ( FIRST : in INTEGER;  
                SECOND : in INTEGER;  
                RESULT : out INTEGER );
```

FIRST	:	in	INTEGER
formal parameter name		parameter mode	parameter type

# Program Units

## Parameter modes

in — The value passed to the subprogram acts as a constant inside and may only be read. Value remains unchanged after completion.

in out — The variable passed to the procedure may be read and updated. Value may change after completion.

out — The variable passed to the procedure may only be updated. Value may change after completion

# Program Units

## procedures

### BODY

- Defines the action to be performed
- Contains a local declarative part
- Contains a sequence of statements

```
procedure ADD ( FIRST : in INTEGER;  
               SECOND : in INTEGER;  
               RESULT : out INTEGER ) is  
    -- local declarations go here  
begin  
    RESULT := FIRST + SECOND;  
end ADD;
```

with ADD;  
procedure SIMPLE\_MATH is

VALUE\_1, VALUE\_2, VALUE\_3 : INTEGER := 5;

begin

ADD ( VALUE\_1, 5, VALUE\_2 );  
ADD ( 10, 20, VALUE\_3 );  
ADD ( VALUE\_1, VALUE\_2, VALUE\_3 );

end SIMPLE\_MATH;

with TEXT\_IO;  
procedure SAY\_HI is

```
MAX_NAME_LENGTH : constant := 80;  
subtype NAME_TYPE is STRING(1..MAX_NAME_LENGTH);  
YOUR_NAME : NAME_TYPE := (others => ' ');  
NAME_LENGTH : NATURAL := 0;
```

begin

```
TEXT_IO.PUT_LINE("What is your name? ");  
TEXT_IO.GET_LINE( YOUR_NAME, NAME_LENGTH );  
TEXT_IO.PUT( "Hi " );  
TEXT_IO.PUT_LINE( YOUR_NAME(1..NAME_LENGTH) );  
TEXT_IO.PUT_LINE( "Have a nice day!!");
```

end SAY\_HI;

# Program Units

procedure AN\_EXAMPLE is

MY\_INTEGER : INTEGER := 10;

TEMP : INTEGER := 0;

procedure NEXT (AN\_INTEGER : in INTEGER;  
VALUE : out INTEGER) is

begin

VALUE := AN\_INTEGER + 1;

end NEXT;

begin

while MY\_INTEGER <= 100 loop

NEXT(MY\_INTEGER,TEMP);

MY\_INTEGER := TEMP;

end loop;

end AN\_EXAMPLE;

# Program Units

## Functions

### SPECIFICATION

- Defines name
- Defines parameters to be passed
- Defines result type

```
function ADD ( FIRST, SECOND : in INTEGER )  
    return INTEGER;
```

- parameter mode can only be "in"
- called as an expression

# Program Units

## Functions

### BODY

- Defines the action to be performed
- Contains a declarative part
- Contains a sequence of statements
- Result returned in a "return" statement

```
function ADD ( FIRST, SECOND : INTEGER )
```

```
    return INTEGER is
```

```
begin
```

```
    return FIRST + SECOND;
```

```
end ADD;
```



# Program Units

## Functions

procedure CALCULATIONS is

VALUE : INTEGER := 1;

function ADD\_PREVIOUS ( NUMBER : in INTEGER )  
return INTEGER is

begin

return NUMBER + ( NUMBER - 1 );

end ADD\_PREVIOUS;

begin

VALUE := ADD\_PREVIOUS ( 5 );

-- value equals 9

end CALCULATIONS;

procedure ADD\_THEN is

type INDEX\_TYPE is range 1 .. 3;

type REAL is digits 9;

type MATRIX\_TYPE is array(INDEX\_TYPE, INDEX\_TYPE)  
of REAL;

function "+" (LEFT, RIGHT : in MATRIX\_TYPE)  
return MATRIX\_TYPE is separate;

FIRST, SECOND,

RESULT : MATRIX\_TYPE := (others => 0.0);

begin

RESULT := FIRST + SECOND;

end ADD\_THEN;

```


separate ( ADD_I THEM )
function "+" ( LEFT, RIGHT : in MATRIX_TYPE ) return
    MATRIX_TYPE is
    TEMP_MATRIX : MATRIX_TYPE := ( others => 0.0 );

begin
    for FIRST_INDEX in MATRIX_TYPE'RANGE(1) loop
        for SECOND_INDEX in MATRIX_TYPE'RANGE(2) loop
            TEMP_MATRIX(FIRST_INDEX, SECOND_INDEX ) :=
                LEFT(FIRST_INDEX,SECOND_INDEX) +
                RIGHT(FIRST_INDEX,SECOND_INDEX);
        end loop;
    end loop;
    return TEMP_MATRIX;
end "+";

```

# Program Units

## Packages



- Defines groups of logically related items
- Structuring tool
- Contains a visible part ( specification ) and a hidden part ( private part and body )
- Primary means for extending the language

# Program Units

## Package specification

-- Define items available to user of package ( export )

package CONSTANTS is

PI : constant := 3.14159;

e : constant := 2.71828;

WARP : constant := 3.00E+08;

-- meters/second

end CONSTANTS;

with CONSTANTS;  
procedure SOME\_PROGRAM is

    MY\_VALUE : FLOAT := 2 \* CONSTANTS.PI;  
begin  
    null;  
end SOME\_PROGRAM;

with CONSTANTS;  
procedure ANOTHER\_PROGRAM is

    ANOTHER\_VALUE : FLOAT := 2 \* CONSTANTS.PI;  
begin  
    null;  
end ANOTHER\_PROGRAM;

# Program Units

```
package ROBOT_CONTROL is
    type SPEED is range 0..100;
    type DISTANCE is range 0..500;
    type DEGREES is range 0..359;
    procedure GO_FORWARD ( HOW_FAST : in SPEED;
                           HOW_FAR : in DISTANCE );
    procedure REVERSE ( HOW_FAST : in SPEED;
                       HOW_FAR : in DISTANCE );
    procedure TURN ( HOW_MUCH : in DEGREES );
end ROBOT_CONTROL;
```

with ROBOT\_CONTROL;

procedure DO\_A\_SQUARE is  
begin

ROBOT\_CONTROL.GO\_FORWARD( HOW\_FAST => 100,  
HOW\_FAR => 20 );

ROBOT\_CONTROL.TURN( 90 );

ROBOT\_CONTROL.GO\_FORWARD( 100, 20 );

ROBOT\_CONTROL.TURN( 90 );

ROBOT\_CONTROL.GO\_FORWARD( 100, 20 );

ROBOT\_CONTROL.TURN( 90 );

ROBOT\_CONTROL.GO\_FORWARD( 100, 20 );

ROBOT\_CONTROL.TURN ( 90 );

end DO\_A\_SQUARE;






# Program Units

## Package bodies

```
--Define local declarations
--Define implementation of subprograms
--- defined in specification
package body ROBOT_CONTROL is
    --local declarations
    procedure RESET_SYSTEM is
begin
    --implementation
    end RESET_SYSTEM;
    procedure GO_FORWARD...is...
    procedure REVERSE...is...
    procedure TURN...is...
end ROBOT_CONTROL;
```

# Program Units



TASK

GENERIC

A program unit that operates in parallel with other program units

Template of a subprogram or package

# Types

--A type consists of a set of values that  
objects of the type may take on, and a  
set of operations applicable to those values

--Ada is a strongly typed language!

- \*Every object must be declared of some type name
- \*Different type names may not be implicitly mixed
- \*Operations on a type must preserve the type

```
AN_INTEGER : INTEGER;  
A_FLOAT_NUMBER : FLOAT;  
ANOTHER_FLOAT : FLOAT;
```


```
A_FLOAT_NUMBER := ANOTHER_FLOAT + AN_INTEGER;  
--illegal
```

# Types

## Types and Objects


### TYPES

Define a template  
for objects



### OBJECTS

Variables or constants  
that are instances  
of a type




### OBJECT DECLARATION


```
MY_INTEGER : INTEGER;
```

```
YOUR_INTEGER : INTEGER := 10;
```

# Ada Types



# Types



← USER DEFINED →

← PREDEFINED →

# Types

## Integers

--Define a set of exact, consecutive values

USER DEFINED

type ALTITUDE is range 0..100\_000;

type DEPTH is range 0..20\_000;

PLANES\_HEIGHT : ALTITUDE;

DIVER\_DEPTH : DEPTH;

begin

PLANES\_HEIGHT := 10\_000;

PLANES\_HEIGHT := 200\_000; -- error

PLANES\_HEIGHT := DIVER\_DEPTH; -- error

end;

# Types

## Predefined integer types

INTEGER----->(usually -32,768..32,767)

"subtypes" of INTEGER

NATURAL(0..INTEGER'LAST)

POSITIVE(1..INTEGER'LAST)

LONG\_INTEGER----->(usually double word)

SHORT\_INTEGER----->(usually half word)



# Types

## Subtypes

- Constrain a range of values or accuracy on a type
- Does not define a new type ,i.e., compatible with base type

```
type ALTITUDE is range 0..200_000;  
subtype HIGH is ALTITUDE range 40_000 .. 200_000;  
subtype MEDIUM is ALTITUDE range 10_000 .. 100_000;  
subtype LOW is ALTITUDE range 0 .. 10_000;
```

# Types

## Enumeration

- Define a set of ordered enumeration values
- Used in array indexing, case statements,
- and looping

### USER DEFINED

```
type SUIT is (CLUBS, HEARTS, DIAMONDS, SPADES);  
type COLOR is (RED, WHITE, BLUE);  
type SWITCH is (OFF, ON);  
type EVEN DIGITS is ('2','4','6','8');  
type MIXED is (ONE,'2',THREE,'*',!,'!',more);
```

where CLUBS < HEARTS < DIAMONDS < SPADES


# Types

Pre-defined enumeration types

BOOLEAN -----> ( FALSE, TRUE )

CHARACTER

# Types



# Types

## Fixed point types

- Absolute bound on error
- Larger error for smaller numbers ( around zero )

### USER DEFINED

type INCREMENT is delta 1.0/8 range 0.0 .. 1.0;

0, 1\*2e-3, 2\*2e-3, 4\*2e-3, 5\*2e-3,...

### PREDEFINED

DURATION ---> (Used for "delay" statements)

# Types

## Floating point types

- Relative bound of error
- Defined in terms of significant digits
- More accurate at smaller numbers, less at larger

### USER DEFINED


type NUMBERS is digits 3 range 0.0 .. 20\_000;

0.001, 0.002, 0.003...9999.0, 1000.0, 1001.0..., 10000.0, 10100.0

### PREDEFINED

FLOAT

# Types



# Types

## Arrays

constrained

unconstrained

### CONSTRAINED

```
-- Indices are static for all objects of that type  
  
type HOURS is range 0..40;  
type DAYS is ( SUN,MON,TUE,WED,THU,FRI,SAT );  
type WORK_HOURS is array( DAYS ) of HOURS;  
  
MY_HOURS : WORK_HOURS := ( 0,8,8,7,6,1,0 );
```

MY_HOURS(SUN)	MY_HOURS(MON)	MY_HOURS(TUE)	MY_HOURS(SAT)
0	8	8	0



# Types

## Arrays

### UNCONSTRAINED

- Indices are known at elaboration (run) time
- Indices may be different for different objects

type HOURS is range 0..40;

type DAYS is (SUN, MON, TUE, WED, THU, FRI, SAT);

type WORK\_HOURS is array (DAYS range <>) of HOURS;

HOLIDAY\_WEEK : WORK\_HOURS (TUE..SAT) :=(others =>0);

FULL\_WEEK : WORK\_HOURS (DAYS'FIRST..DAYS'LAST);

# Types

procedure DAYS\_WORKED (FIRST,SECOND: in DAYS) is

    A\_WEEK : WORK\_HOURS (FIRST..SECOND);

begin

    .

    .

    .

DAYS\_WORKED(WED,FRI);



DAYS\_WORKED(FRI,SAT);



# Types

## Multi--dimensional arrays

```
type VALUES is digits 6 range -10.0 .. 100.0;
type INDEX is range 1..3;
type TWO_D_MATRIX is array (INDEX,INDEX) of VALUES;

MY_MATRIX : TWO_D_MATRIX := ( others => 0.0 );
IDENTITY_MATRIX : constant TWO_D_MATRIX := ( (1.0,0.0,0.0),
                                              (0.0,1.0,0.0),
                                              (0.0,0.0,1.0));
```

begin

```
MY_MATRIX := IDENTITY_MATRIX;
MY_MATRIX (3,3) := 2.0;
```

.  
.  
.

# Types

## Array

### PREDEFINED

type STRING is array (POSITIVE range <>) of CHARACTER;

### USE OF THE PREDEFINED STRING TYPE

YOUR\_STRING : STRING (1..10);

MY\_STRING : STRING (1..20);

THEIR\_STRING : STRING; -- illegal

### STRING SLICING

YOUR\_STRING := MY\_STRING(1..10);

MY\_STRING(11..15) := YOUR\_STRING(2..6);

MY\_STRING(3..4) := MY\_STRING(4..5);

MY\_STRING(2) := 'G';

MY\_STRING(2) := "G"; -- illegal

# Types

## Records

undiscriminated  
discriminated  
variant

### UNDISCRIMINATED

type DAYS is ( MON,TUE,WED,THU,FRI,SAT,SUN );  
type DAY is range 1..31;  
type MONTH is ( JAN,FEB,MAR,APR,MAY,JUN,JUL,AUG,  
SEP,OCT,NOV,DEC);

type YEAR is range 0..2085;

type DATE is record

DAY\_OF\_WEEK : DAYS;

DAY\_NUMBER : DAY;

MONTH\_NAME : MONTH;

YEAR\_NUMBER : YEAR;

end record;

TODAY : DATE;

begin

TODAY.DAY\_OF\_WEEK := TUE;

TODAY.DAY\_NUMBER := 26;

TODAY.MONTH\_NAME := NOV;

TODAY

DAY_OF_WEEK	TUE
DAY_NUMBER	26
MONTH_NAME	NOV
YEAR_NUMBER	1985

## Types

## Records

```
type A_MONTH is array (DAY range <>) of DATE;  
NOVEMBER: A_MONTH(1..30);
```

```
begin
```

```
    NOVEMBER(26).DAY_OF_WEEK := TUE;  
    NOVEMBER(27) := (WED,27,NOV,1985);
```

# Types

## Records

### DISCRIMINATED

```
type BUFFER(SIZE:POSITIVE := 10) is record
    ITEMS : STRING(1..SIZE);
end record;
```

```
MY_BUFFER : BUFFER; -- size is 10;
YOUR_BUFFER : BUFFER (20);
THEIR_BUFFER : BUFFER (SIZE => 15);
```

```
begin
    MY_BUFFER.ITEMS := "Hi There!!";
```

# Types

## Records

### VARIANT

```
type DRIVER is (GOOD,BAD);
type INSURANCE_RATE is range 1..50;
type DISCOUNT is delta 0.01 range 0.0..1.0;
type INSURANCE (KIND:DRIVER) is record
    NORMAL_RATE : INSURANCE_RATE;
    case KIND is
        when GOOD => DISCOUNT_RATE : DISCOUNT ;
        when BAD => ADDITIONAL : INSURANCE_RATE;
    end case;
end record;
```



# Types

## Records


### VARIANT

```
type DRIVER is (GOOD,BAD);
type INSURANCE_RATE is range 1..50;
type DISCOUNT is delta 0.01 range 0.0..1.0;
type INSURANCE (KIND:DRIVER) is record
    NORMAL_RATE : INSURANCE_RATE;
    case KIND is
        when GOOD => DISCOUNT_RATE : DISCOUNT ;
        when BAD => ADDITIONAL : INSURANCE_RATE;
    end case;
end record;
```

# Types

Access types— Linked list

--Move current pointer  
CURRENT := TEMP;




# Types

## Private types

- Defined in a package
- Used to create abstract data types
- Used to extend the language
- Directly supports abstraction and
- Information hiding

INTEGER\_STACK



PRIVATE

$:=$   $=$   $/=$

subprograms defined in  
package specification

LIMITED PRIVATE

only subprograms  
defined in  
package specification

# Types


## Access types – Linked list

```
procedure LINKED LIST is  
  type ITEM; -- incomplete type declaration  
  type POINTER is access ITEM;  
  type ITEM is record  
    NAME: STRING(1..20):=(others => ' ');  
    NEXT : POINTER;  
  end record;
```

```
  HEAD,CURRENT,TEMP:POINTER; --initialized to null
```

```
begin
```

```
  HEAD:=new ITEM;  
  CURRENT:=HEAD;
```




```
  CURRENT.NAME(1..3):= "Bob";
```

# Types

## Access types – Linked list


Create a New Item

```
TEMP := new ITEM;  
TEMP.NAME(1..4) := "MARY";
```



Add to List

```
CURRENT.NEXT := TEMP;
```



package BASKIN\_ROBBINS is

type NUMBERS is range 0 .. 99;

procedure TAKE( A\_NUMBER : out NUMBERS );

procedure NOW\_SERVING return NUMBERS;

procedure SERVE( A\_NUMBER : in NUMBERS );

end BASKIN\_ROBBINS;

with BASKIN\_ROBBINS;

procedure GET\_ICE\_CREAM is

YOUR\_NUMBER : BASKIN\_ROBBINS.NUMBERS;

begin

BASKIN\_ROBBINS.TAKE( YOUR\_NUMBER );

loop

if BASKIN\_ROBBINS."="( BASKIN\_ROBBINS.NOW\_SERVING,  
YOUR\_NUMBER );

BASKIN\_ROBBINS.SERVE( YOUR\_NUMBER );

exit;

end if;

end loop;

end GET\_ICE\_CREAM;

with BASKIN\_ROBBINS; use BASKIN\_ROBBINS;  
procedure GET\_ICE\_CREAM is

YOUR\_NUMBER : BASKIN\_ROBBINS.NUMBERS;

begin

BASKIN\_ROBBINS.TAKE( YOUR\_NUMBER );

loop

if BASKIN\_ROBBINS.NOW\_SERVING = YOUR\_NUMBER then  
    BASKIN\_ROBBINS.SERVE( YOUR\_NUMBER );  
    exit;

else

YOUR\_NUMBER := YOUR\_NUMBER - 1;

end if;

end loop;

end GET\_ICE\_CREAM;



package BASKIN\_ROBBINS is

type NUMBERS is private;

procedure TAKE( A\_NUMBER : out NUMBERS );

procedure NOW\_SERVING return NUMBERS;

procedure SERVE( A\_NUMBER : in NUMBERS );

private

type NUMBERS is range 0 .. 99;

end BASKIN\_ROBBINS;

with BASKIN\_ROBBINS; use BASKIN\_ROBBINS;  
procedure GET\_ICE\_CREAM is

YOUR\_NUMBER : BASKIN\_ROBBINS.NUMBERS;

begin

BASKIN\_ROBBINS.TAKE( YOUR\_NUMBER );

loop

if BASKIN\_ROBBINS.NOW\_SERVING = YOUR\_NUMBER then  
    BASKIN\_ROBBINS.SERVE( YOUR\_NUMBER );  
    exit;

else

YOUR\_NUMBER := BASKIN\_ROBBINS.NOW\_SERVING;

end if;

end loop;

end GET\_ICE\_CREAM;

```
package BASKIN_ROBBINS is

    type NUMBERS is limited private;

    procedure TAKE( A_NUMBER : out NUMBERS );

    procedure NOW_SERVING return NUMBERS;

    procedure SERVE( A_NUMBER : in NUMBERS );

    function "="( LEFT, RIGHT : NUMBERS) return BOOLEAN;

private

    type NUMBERS is range 0 .. 99;

end BASKIN_ROBBINS;
```

```
with BASKIN_ROBBINS; use BASKIN_ROBBINS;  
procedure GET_ICE_CREAM is  
  YOUR_NUMBER : BASKIN_ROBBINS.NUMBERS;  
  procedure GO_TO_DAIRY_QUEEN is separate;  
begin  
  BASKIN_ROBBINS.TAKE( YOUR_NUMBER );  
  loop  
    if BASKIN_ROBBINS.NOW_SERVING = YOUR_NUMBER then  
      BASKIN_ROBBINS.SERVE( YOUR_NUMBER );  
      exit;  
    else  
      GO_TO_DAIRY_QUEEN;  
      exit;  
    end if;  
  end loop;  
end GET_ICE_CREAM;
```

# Types

## Private types

```
package INTEGER_STACK is
  type STACK is limited private;
  procedure POP ( ITEM : out INTEGER;
                 OFF_OF:in out STACK);
  procedure PUSH (ITEM: in INTEGER;
                  ON: in out STACK);
private
  --Define what a stack looks like
end INTEGER_STACK;
```

# Types

## Private types

```
with INTEGER_STACK;  
use INTEGER_STACK;  
procedure STACK_THEM is  
    MY_STACK, YOUR_STACK: STACK;  
    AN_ITEM: INTEGER  
begin  
    PUSH (ITEM=>20, ON=>MY_STACK);  
    PUSH (ITEM=>30, ON=>YOUR_STACK);  
    PUSH (40, ON=>MY_STACK);  
    .  
    .  
    . POP (AN_ITEM, OFF_OF=>MY_STACK);  
    --AN_ITEM = 40  
end STACK_THEM;
```

# Control Statements

SEQUENTIAL -----	CONDITIONAL -----	ITERATIVE -----
ASSIGNMENT	IF	LOOP
PROCEDURE CALL	CASE	
RETURN		
NULL		
BLOCK		
TASKING -----	OTHERS -----	
ENTRY CALL	GOTO	
DELAY	RAISE	
ABORT	CODE	
ACCEPT		
SELECT		

# Control Statements

## Sequential

### ASSIGNMENT

-- Replaces variable on left with expression on right  
AN\_INTEGER := ( 5\*2) + 34;

### PROCEDURE CALL

-- Executes a procedure  
POP ( AN\_INTEGER, OFF\_OF => MY\_STACK );

### NULL

-- Explicitly does nothing  
null;



# Control Statements

## Sequential

### RETURN

-- Causes control to be passed back to the caller  
of a subprogram

For a procedure...

procedure A\_PROCEDURE is

    AN\_INTEGER : INTEGER;

begin

    AN\_INTEGER := 5;

return;

    null; -- never gets executed

end A\_PROCEDURE;

# Control Statements

## Sequential

### RETURN

-- For a function, returns a value

```
function IS_GREATER ( FIRST, SECOND : in INTEGER )  
    return BOOLEAN;
```

begin

```
    return ( FIRST > SECOND );  
end IS_GREATER;
```

-- Every function must have at least one  
 return statement

# Control Statements

## Sequential

### BLOCK

-- Used to localize declarations and/or effects

procedure MAIN\_PROGRAM is

VARIABLE : FLOAT;

begin

-- some statements

declare

LOCAL\_VARIABLE : FLOAT;

begin

LOCAL\_VARIABLE := 4.0;

VARIABLE := 70.0;

end;

VARIABLE := 10.0;

end MAIN\_PROGRAM;

# Control Statements

## Conditional

IF

```
if MY_VALUE = 27 then  
    HIS_VALUE := 21;  
    THEIR_VALUE := 22;  
end if;
```

```
if MACHINE_IS_RUNNING then  
    SET_NEW_SPEED ( 47 );  
else  
    COUNT_TIME_DOWN ( CURRENT_TIME );  
end if;
```

# Control Statements

## Conditional

IF

```
if MACHINE_IS_RUNNING then
    SET_NEW_SPEED ( 47 );
elseif MACHINE_IS_IDLE then
    START_MACHINE_UP;
else
    COUNT_TIME_DOWN ( CURRENT_TIME );
end if;
```

# Control Statements

## Conditional

```
type DAY_TIMES is ( EARLY_AM,MID_AM,LUNCH,AFTERNOON,  
                    LATE_AFTERNOON,DINNER,EVENING,NIGHT );
```

```
TIME : DAY_TIMES := AFTERNOON;
```

```
begin
```

```
  if TIME = EARLY_AM then
```

```
    DRINK_COFFEE;
```

```
  elsif TIME = MID_AM then
```

```
    DRINK_COFFEE;
```

```
  elsif TIME = LUNCH then
```

```
    GO_EAT;
```

```
  elsif TIME = AFTERNOON then
```

```
    STAY_AWAKE;
```

```
  elsif TIME = LATE_AFTERNOON then
```

```
    GET_READY_TO_GO_HOME;
```

```
  else
```

```
    GET_READY_FOR_TOMMORROW;
```

```
  end if;
```

```
end;
```

# Control Statements

## Conditional

### CASE

```
case TIME is
  when EARLY_AM | MID_AM => DRINK_COFFEE;
  when LUNCH => GO_EAT;
  when AFTERNOON => STAY_AWAKE;
  when LATE_AFTERNOON => GET_READY_TO_GO_HOME;
  when others => GET_READY_FOR_TOMMORROW;

end case;
```

# Control Statements

## Iterative

### BASIC LOOP

```
loop
  -- statements
end loop;
```

### EXIT STATEMENT

```
loop
  if X = 20 then
    exit;
  end if;
end loop;
```

```
loop
  if X = 20 then
    exit;
  end if;
end loop;
end loop;
end loop;
```



# Control Statements

## Iterative

OUTER:  
loop

INNER:  
loop  
if  $X = 20$  then  
    exit OUTER;  
end if;  
exit INNER when  $X = 21$ ;  
 $X := X + 2$ ;  
end loop INNER;  
end loop OUTER;

# Control Statements

## Iterative

### FOR LOOP ITERATION SCHEME

```
with TEXT_IO; use TEXT_IO;
procedure PRINT_ALL_VALUES is
type COLORS is ( RED, WHITE, BLUE );
package COLOR_IO is new ENUMERATION_IO ( COLORS );
use COLOR_IO;

begin
  for INDEX in 1..5 loop
    null;
  end loop;

  for A_COLOR in COLORS loop
    PUT ( A_COLOR );
    NEW_LINE;
  end loop;
end PRINT_ALL_VALUES;
```

# Control Statements

## Iterative

```
for MY_INDEX in 20..40 loop
  -- some statements
end loop;
```

```
for YOUR_INDEX in reverse 20..40 loop
  -- some statements
end loop;
```

# Control Statements


## Iterative

### WHILE LOOP ITERATION SCHEME

```
while NOT_DARK loop
    PLAY_TENNIS;
end loop;
TURN_ON_LIGHTS;
```

# Exceptions

- Real time systems must have the ability to handle error situations to be reliable



- Exceptions deal with exceptional situations

# Exceptions

```
with TEXT_IO; use TEXT_IO;
procedure GET_NUMBERS is
type NUMBERS is range 1..100;
package NUM_IO is new INTEGER_IO ( NUMBERS );
use NUM_IO;
A_NUMBER : NUMBERS;
begin
loop
GET ( A_NUMBER );
NEW_LINE;
PUT("The number is ");
PUT ( A_NUMBER );
NEW_LINE;
end loop;
exception
when DATA_ERROR => PUT_LINE("That was a bad number");
end GET_NUMBERS;
```

# Exceptions

- When an exception situation occurs, the exception is said to be "raised"
- What happens then, depends on the presence or absence of an exception handler

```
begin
  loop
    GET ( A_NUMBER );
    NEW_LINE;
    PUT("The number is");
    PUT ( A_NUMBER );
    NEW_LINE;
  end loop;
end GET_NUMBERS;
```

# Exceptions

```
begin
loop
begin
  GET ( A_NUMBER );
  NEW_LINE;
  PUT ( "The number is " );
  PUT ( A_NUMBER );
  NEW_LINE;
exception
  when DATA_ERROR => PUT_LINE("Bad number, try again");
end;
end loop;
end GET_NUMBERS;
```



# Exceptions

USER DEFINED

PREDEFINED

STACK\_OVERFLOW : exception;

CONSTRAINT\_ERROR

BAD\_INPUT : exception;

NUMERIC\_ERROR

DEAD\_SENSOR : exception;

PROGRAM\_ERROR

STORAGE\_ERROR

TASKING\_ERROR

## I/O EXCEPTIONS

STATUS\_ERROR

MODE\_ERROR

NAME\_ERROR

USE\_ERROR

DEVICE\_ERROR

END\_ERROR

DATA\_ERROR

package SIMPLE\_STACK is

type STACK\_TYPE is limited private;  
subtype ELEMENT\_TYPE is CHARACTER;

procedure PUSH ( AVALUE : in ELEMENT\_TYPE;  
                  STACK : in out STACK\_TYPE );

procedure POP ( AVALUE : out ELEMENT\_TYPE;  
                STACK : in out STACK\_TYPE );

STACK\_OVERFLOW, STACK\_UNDERFLOW : exception;

private

type STACK\_ITEM;  
type STACK\_TYPE is access STACK\_ITEM;  
type STACK\_ITEM is record  
    VALUE : ELEMENT\_TYPE;  
    NEXT : STACK\_TYPE;  
end record;

end SIMPLE\_STACK;

NO-A190 365

TUTORIAL TRACK I INTRODUCTION TO ADA(U) INFORMATION  
SYSTEMS AND TECHNOLOGY CENTER W-P AFB OH ADA VALIDATION  
FACILITY C ENGLE ET AL 09 JUN 87


2/2


UNCLASSIFIED

F/G 12/5

NL

4





MICROCOPY RESOLUTION TEST CHART  
NATIONAL BUREAU OF STANDARDS-1963-A

separate ( SIMPLE\_STACK )  
procedure POP ( A\_VALUE : out ELEMENT\_TYPE;  
                  A\_STACK : in out STACK\_TYPE ) is

begin

    A\_VALUE := A\_STACK.VALUE;  
    A\_STACK := A\_STACK.NEXT;

exception

    when CONSTRAINT\_ERROR =>  
        raise STACK\_UNDERFLOW;

end POP;

separate ( SIMPLE\_STACK )  
procedure PUSH ( A\_VALUE : in ELEMENT\_TYPE;  
                  A\_STACK : in out STACK\_TYPE ) is

TEMP\_ITEM : STACK\_TYPE;

begin

TEMP\_ITEM := new STACK\_TYPE;  
TEMP\_ITEM.NEXT := A\_STACK;  
TEMP\_ITEM.VALUE := A\_VALUE;  
A\_STACK := TEMP\_ITEM;

exception

when STORAGE\_ERROR =>  
    raise STACK\_OVERFLOW;

end PUSH;

with TEXT\_IO, SIMPLE\_STACK;  
procedure STACK\_USER is

package COUNT\_IO is new TEXT\_IO.INTEGER\_IO(LONG\_INTEGER);

MY\_STACK : SIMPLE\_STACK.STACK\_TYPE;  
COUNTER : LONG\_INTEGER := 0;

begin

loop

SIMPLE\_STACK.PUSH('a', MY\_STACK);  
COUNTER := COUNTER + 1;

end loop;

exception

when SIMPLE\_STACK.STACK\_OVERFLOW =>  
TEXT\_IO.PUT("Pushed");  
COUNT\_IO.PUT(COUNTER);  
TEXT\_IO.PUT\_LINE(" times");

end STACK\_USER;

# Generics

Parameterized Program Unit  
subprograms  
packages

Cannot be called

Must be instantiated



# Generics

## Data Objects

- To define the template: use type declaration
- To define an instance: use object declaration

## Generic program units

- To define the template: use generic declaration
- To define an instance: use generic instantiation

# Generics

Generics Provide:

- factorization
- reduction in size of program text
- more compact code
- no unnecessary duplication of source
- maintainability
- readability
- efficiency

# Generics

procedure INTEGER\_SWAP (FIRST\_INTEGER, SECOND\_INTEGER:  
in out INTEGER) is

TEMP : INTEGER;

**begin**

```
TEMP      := FIRST_INTEGER;  
FIRST_INTEGER := SECOND_INTEGER;  
SECOND_INTEGER := TEMP;
```

end INTEGER\_SWAP;

# Generics

generic

type ELEMENT is private;

procedure SWAP (ITEM\_1,ITEM\_2:in out ELEMENT);

procedure SWAP(ITEM\_1,ITEM\_2:in out ELEMENT) is

TEMP:ELEMENT;

begin

TEMP := ITEM\_1;

ITEM\_1 := ITEM\_2;

ITEM\_2 := TEMP;

end SWAP;

# Generics

with SWAP;

procedure EXAMPLE is

    procedure INTEGER\_SWAP is new SWAP(INTEGER);

    procedure CHARACTER\_SWAP is new SWAP(CHARACTER);

    NUM\_1, NUM\_2 : INTEGER;

    CHAR\_1, CHAR\_2 : CHARACTER;

begin

    NUM\_1 := 10;

    NUM\_2 := 25;

    INTEGER\_SWAP(NUM\_1, NUM\_2 );

    CHAR\_1 := 'A';

    CHAR\_2 := 'S';

    CHARACTER\_SWAP(CHAR\_1, CHAR\_2);

end EXAMPLE;

## Generics

```
generic
  type DISCRETE_TYPE is (<>);
function NEXT(VALUE : in DISCRETE_TYPE)
  return DISCRETE_TYPE;
function NEXT(VALUE : in DISCRETE_TYPE)
  return DISCRETE_TYPE is
begin
  if VALUE = DISCRETE_TYPE'LAST then
    return DISCRETE_TYPE'FIRST
  else
    return DISCRETE_TYPE'SUCC(VALUE);
  end if;
end NEXT;
```

# Generics

```
with NEXT;
with TEXT_IO; use TEXT_IO;
procedure MAIN_DRIVER is

  type DAYS is (MON, TUE, WED, THUR, FRI, SAT, SUN);
  TODAY, TOMORROW : DAYS;
  package DAYS_IO is new ENUMERATION_IO (DAYS);
  function DAY_AFTER is new NEXT (DAYS);

begin
  PUT ("Enter the day: ");
  DAYS_IO.GET (TODAY);
  TOMORROW := DAY_AFTER (TODAY);
  PUT ("Tomorrow is: ");
  DAYS_IO.PUT (TOMORROW);

end MAIN_DRIVER;
```

# Generics

```
with NEXT;
with TEXT_IO; use TEXT_IO;
procedure MAIN_DRIVER_2 is

    type HOUR is range 1..12;
    THIS_HOUR, NEXT_HOUR : HOUR;
    package HOUR_JO is new ENUMERATION_JO (HOUR);
    function HOUR_AFTER is new NEXT (HOUR);

begin

    PUT ("The current hour is: ");
    HOUR_JO.GET (THIS_HOUR);
    NEXT_HOUR := HOUR_AFTER(THIS_HOUR);
    PUT ("Next hour is: ");
    HOUR_JO.PUT (NEXT_HOUR);

end MAIN_DRIVER_2;
```



# Generics

generic

SIZE: in POSITIVE;  
type ELEMENT is private;

package STACK is

STACK\_UNDERFLOW,  
STACK\_OVERFLOW : exception;  
procedure PUSH (ITEM:in ELEMENT);  
procedure POP (ITEM:in out ELEMENT);

end STACK;

# Generics

package body STACK is

SPACE: array (1..SIZE) of ELEMENT;

TOP: INTEGER range 0..SIZE:= 0;

procedure PUSH(ITEM:in ELEMENT)is  
begin

if TOP = SIZE then

raise STACK\_OVERFLOW;

end if;

TOP := TOP +1;

SPACE(TOP) := ITEM;

end PUSH;

procedure POP(ITEM:in out ELEMENT) is

begin

if TOP = 0 then

raise STACK\_UNDERFLOW;

end if;

ITEM := SPACE(TOP);

TOP := TOP -1;

end POP;

end STACK;

# Generics

```
with STACK;
with TEXT_IO; use TEXT_IO;
procedure STACK_OPS is

    package INT_IO is new INTEGER_IO (POSITIVE);
    use INT_IO;
    INT_ELEMENT : POSITIVE;
    STACK_SIZE : POSITIVE := 50;
    package INTEGER_STACK is new STACK
        (STACK_SIZE, POSITIVE);
    use INTEGER_STACK;

begin
    PUT ("Enter an element to push on the stack: ");
    GET (INT_ELEMENT);
    PUSH (INT_ELEMENT);
    POP (INT_ELEMENT);
    PUT ("The element popped off the stack was: ");
    PUT (INT_ELEMENT);
```

# Generics

```
with STACK, TEXT_IJO; use TEXT_IJO;
procedure STACK_OPS_2 is

    STACK_SIZE : POSITIVE := 50;
    INT_ELEMENT : POSITIVE;
    FLOAT_ELEMENT : FLOAT;

    package INT_IJO is new INTEGER_IJO (POSITIVE);
    package REAL_IJO is new FLOAT_IJO (FLOAT);
    package INT_STACK is new STACK (STACK_SIZE, POSITIVE);
    package FLOAT_STACK is new STACK (100, FLOAT);

    use INT_IJO, REAL_IJO, INT_STACK, FLOAT_STACK;

begin

    PUT ("Enter a positive element to push on the stack: ");
    GET (INT_ELEMENT);
    PUSH (INT_ELEMENT);

    PUT ("Enter a FLOAT element to push on the stack: ");
    GET (FLOAT_ELEMENT);
    PUSH (FLOAT_ELEMENT);

end STACK_OPS_2;
```

# Generics

generic

type ELEM is private;

with function "\*" (LEFT, RIGHT : ELEM)

return ELEM is < >;

function SQUARING (X : ELEM) return ELEM;

function SQUARING (X : ELEM) return ELEM is

begin

return X \* X;

end SQUARING;

# Generics

```
with SQUARING;  
procedure MATH_PROGRAM is  
  
    function SQUARE is new SQUARING (INTEGER);  
    X : INTEGER := 8;  
  
begin  
  
    X := SQUARE (X);  
  
end MATH_PROGRAM;
```


# Generics

```
with SQUARING;  
procedure MATH_PROGRAM_2 is  
  type MATRIX is array (1..3, 1..3) of INTEGER;  
  A_MATRIX : MATRIX :=  
    (others => (others => 2));  
  function MULT (LEFT, RIGHT : MATRIX) return  
    MATRIX is separate;  
  function SQUARE_A_MATRIX is new SQUARING  
    (MATRIX, MULT);  
begin  
  A_MATRIX := SQUARE_A_MATRIX (A_MATRIX);  
end MATH_PROGRAM_2;
```

```
generic
    type ELEMENT_TYPE is private;
    procedure SWAP ( LEFT, RIGHT : in out ELEMENT_TYPE );
    procedure SWAP ( LEFT, RIGHT : in out ELEMENT_TYPE ) is
        TEMP_ELEMENT : ELEMENT_TYPE := LEFT;
    begin
        LEFT := RIGHT;
        RIGHT := TEMP_ELEMENT;
    end SWAP;
```




# Tasks



- A task is an entity that operates in parallel with other entities
- Tasking may be implemented on
  - Single Processors
  - Multi-processors
  - Multi-computers

# Tasks



# Tasks

```
procedure SENSOR_CONTROLLER is
```

```
function OUT_OF_LIMITS return BOOLEAN;  
procedure SOUND_ALARM;
```

```
task MONITOR_SENSOR; --- specification  
task body MONITOR_SENSOR is --- body  
begin
```

```
    loop
```

```
        if OUT_OF_LIMITS then
```

```
            SOUND_ALARM;
```

```
        end if;
```

```
    end loop;
```

```
end MONITOR_SENSOR;
```

```
function OUT_OF_LIMITS return BOOLEAN is separate;  
procedure SOUND_ALARM is separate;
```

```
begin
```

```
    null; --- Task is activated here
```

```
end SENSOR_CONTROLLER;
```

# Tasks

```
-- a basic task with no communication
with TEXTJO; use TEXTJO;
procedure COUNT_NUMBERS is
package INTJO is new INTEGERJO (INTEGER);
use INTJO;
task COUNT_SMALL;
task COUNT_LARGE;

task body COUNT_SMALL is
begin
  for INDEX in -100..0 loop
    PUT(INDEX);
    NEW_LINE;
  end loop;
end COUNT_SMALL;

task body COUNT_LARGE is
begin
  for INDEX in 0..100 loop
    PUT(INDEX);
    NEW_LINE;
  end loop;
end COUNT_LARGE;

begin
  null; --tasks are started here
end COUNT_NUMBERS;
```

# Tasks

```
--Tasks can communicate with each other  
-- via parameters defined in entries
```

```
task CHANNEL is  
    entry PRINT(JOB:in JOB_NUMBER);  
end CHANNEL;
```

```
--To communicate use an "entry" call  
CHANNEL.PRINT(24);
```

```
--When two tasks are synchronized in time  
-- and are communicating, we say that the  
-- two tasks are in "rendezvous"
```

# Tasks

--Inside a task, rendezvous occurs when  
-- a task's entry has been called and  
-- an accept statement is reached

task body CHANNEL is

    LOCAL\_NUMBER : JOB\_NUMBER;

begin

    loop

        accept PRINT(JOB:in JOB\_NUMBER)do

            LOCAL\_NUMBER := JOB;

        end;


        CALL\_PRINTER (LOCAL\_NUMBER);

    end loop;

end CHANNEL;


# Tasks

## STAGES OF A RENDEZVOUS (ENTRY CALL FIRST)



# Tasks

## STAGES OF A RENDEZVOUS (ACCEPT FIRST)





# Tasks

Tasking statements

---

ENTRY CALL  
DELAY  
ABORT  
ACCEPT  
SELECT

# Tasks

## DELAY -----

- Used to suspend execution for at least
- the time interval specified
- delay 30.0;

## ABORT -----

- Used to unconditionally terminate a task
- Only used in extreme circumstances
- abort CHANNEL;

# Tasks

SELECT  
-----

```
--Used to choose between entries in a task
task DRIVE_CONTROL is
    entry READ(DATA: out DATA_TYPE);
    entry WRITE(DATA: in DATA_TYPE);
end DRIVE_CONTROL;

task body DRIVE_CONTROL is
begin
    loop
        select
            accept READ(DATA:out DATA_TYPE)do
                .
            end;
        or
            accept WRITE(DATA:in DATA_TYPE)do
                .
            end;
        end select;
    end loop;
```

```
with LIST_PACKAGE, TEXTJO;  
use LIST_PACKAGE, TEXTJO;  
procedure ORDERLIST is
```

```
    UNSORTED_FILE : FILE_TYPE;  
    SORTED_FILE : FILE_TYPE;
```

```
    MAX_ITEMS : constant := 20;
```

```
    THE_LIST : ALIST(1..MAX_ITEMS);  
    LIST_INDEX : POSITIVE := 1;
```

```
    LAST : NATURAL;  
    FILE_NAME : STRING(1..40);
```

```
begin
    PUT_LINE ("This program sorts a list of names, addresses and ");
    PUT_LINE ("phone numbers and puts that sorted list in a file.");
    NEW_LINE (2);
    PUT_LINE ("What is the name of the file to sort?");
    GET_LINE (FILE_NAME, LAST);
    OPEN (UNSORTED_FILE, IN_FILE, FILE_NAME (1..LAST));
    while not END_OF_FILE (UNSORTED_FILE) loop
        GET_LINE (UNSORTED_FILE, THE_LIST (LIST_INDEX).NAME, LAST);
        GET_LINE (UNSORTED_FILE, THE_LIST (LIST_INDEX).ADDRESS, LAST);
        GET_LINE (UNSORTED_FILE, THE_LIST (LIST_INDEX).PHONE_NUMBER, LAST);
        LIST_INDEX := LIST_INDEX + 1;
    end loop;
    SORT (THE_LIST (1..LIST_INDEX - 1));
    CLOSE (UNSORTED_FILE);
```

package LIST\_PACKAGE is

MAX\_LINE\_LENGTH : constant := 80;

subtype ALINE is STRING(1..MAX\_LINE\_LENGTH);

type ITEMS is record

NAME : ALINE := ( others => '' );

ADDRESS : ALINE := ( others => '' );

PHONE\_NUMBER := ( others => '' );

end record;

type ALLIST is array( POSITIVE range <> ) of ITEMS;

procedure SORT ( ANY\_LIST : in out ALLIST );

end LIST\_PACKAGE;

```

with SWAP;
package body LIST_PACKAGE is

  procedure SWAP_ITEMS is new SWAP ( ELEMENT_TYPE => ITEMS );

  procedure SORT ( ANY_LIST : in out A_LIST ) is
  -- implements a selection sort
    SMALLEST_INDEX, TEMP_INDEX : POSITIVE;
    SMALLEST_NAME : A_LINE := ( others => ' ' );

  begin
    for SORTED_INDEX in ANY_LIST'RANGE loop
      SMALLEST_INDEX := SORTED_INDEX;
      for CHECK_INDEX in (SORTED_INDEX+1)..ANY_LIST'LAST loop
        if ANY_LIST ( CHECK_INDEX).NAME <
           ANY_LIST (SMALLEST_INDEX).NAME then
          SMALLEST_INDEX := CHECK_INDEX;
        end if;
      end loop;
      SWAP_ITEMS ( ANY_LIST(SMALLEST_INDEX),
                   ANY_LIST(SORTED_INDEX) );
    end loop;
  end SORT;

end LIST_PACKAGE;

```

```
PUT_LINE("What is the name of the file to output to?");
GET_LINE( FILE_NAME, LAST );

CREATE ( SORTED_FILE, OUT_FILE, FILE_NAME(1..LAST) );

for FILE_ITEM in 1 .. LIST_INDEX - 1 loop

    PUT_LINE( SORTED_FILE,THE_LIST(FILE_ITEM).NAME );
    PUT_LINE(SORTED_FILE,THE_LIST(FILE_ITEM).ADDRESS );
    PUT_LINE(SORTED_FILE,THE_LIST(FILE_ITEM).PHONE_NUMBER);

    NEW_LINE(SORTED_FILE);

end loop;

CLOSE ( SORTED_FILE );

end ORDER_LIST;
```



END

DATE

FILMED

5-88

DTIC